






Product Information	Data
Category	LED Panels
Name	Milo 600
Codex Code	COPL/MI2840
Image	
Features & Benefits	<p>Exceptionally efficient attractive panel unit with lightweight aluminium frame</p> <p>Using indirect lighting for down light and visual comfort</p> <p>Simple installation</p> <p>Emergency and motion sensor options</p> <p>Up to 70% energy saving</p> <p>Instant, uniform light output, no flicking and unlimited switching</p> <p>LED lifespan L70 75,000 hours</p>
At a glance	
IP Rating	IP65/ IP20 Rear
Colour/ Finish	White
Mounting Method	Ceiling
Warranty (Years)	5
TECHNICAL DATA	
Wattage (W)	28

Product Information	Data
Light Source	2835
Number of LED's	108
Operating Lifespan (Hours)	35,000
Colour Temperature CCT (K)	4000
CRI	>80
Luminous Flux (Lm)	3360
Lumens/Watt (Lm/W)	120
Input Voltage/ Frequency	AC220~240V 50/60Hz
Class Protection	Class 2
Operating Temperature Range (degrees C)	minus 20 plus 40
Dimensions	
Detail Dimensions	H 595 x W 595 x D 35.6mm
Motion Sensor	NO
Motion Sensor Technical Data	N/A
Corridor Function	NO
3 Step Dimming	NO
Lux Sensor	NO
Photocell Advance	NO
Adjustable Controls	NO

Product Information	Data
Emergency	NO
Replaceable Plug In Light Source	N/A
Replaceable Emergency Pack	N/A
Battery Warranty (years)	N/A
Other Options	Please contact us for further CCT and size options
Related Products	



www.codexled.co.uk

01223 393754

info@codexled.co.uk

